

## **AMENDMENTS TO THE CLAIMS**

1. (Canceled)
2. (Canceled)
3. (Currently Amended) The diafiltration module according to claim 2 7, wherein the control unit is responsive to a second detected characteristic of blood within the extracorporeal circuit, the second detected characteristic being a flow rate of the blood, wherein the control unit is configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the second detected characteristic meets a prescribed criteria.
4. (Currently Amended) The diafiltration module according to claim 3, further including:
  - a first flow meter disposed within the first conduit for detecting a flow rate of ~~one of the dialysate fluid within the first conduit and the diverted dialysate fluid within the second conduit~~, wherein the detected flow rate comprises the first detected characteristic, the first flow meter in communication with the control unit; and
  - a second flow meter disposed within the extracorporeal circuit for detecting a flow rate of the blood, the second flow meter in communication with the control unit, wherein the detected flow rate of blood comprises the second detected characteristic.
5. (Canceled)
6. (Canceled)
7. (Currently Amended) In a blood dialysis system including a dialysis machine and an extracorporeal circuit including a dialyzer, a diafiltration

module that is an independent standalone unit relative to the dialysis machine and the extracorporeal circuit and is adapted to be detachably connected to at least one of the dialysis machine and the extracorporeal circuit, the diafiltration module comprising:

a first conduit having a first end and an opposing second end, the first end for receiving a dialysate fluid from the dialysis machine and the second end for discharging the dialysate fluid to the dialyzer;

a second conduit in selective communication with the first conduit such that the second conduit selectively receives a diverted amount of the dialysate fluid from the first conduit, the second conduit communicating with at least one sterilizing filter for filtering the diverted amount of the dialysate fluid to produce a substitution fluid, wherein one end of the second conduit is configured to deliver the substitution fluid to the extracorporeal circuit;

a control unit responsive to a first detected characteristic of one of the dialysate fluid flowing within the first conduit and the diverted dialysate fluid flowing within the second conduit, the control unit being configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the first detected characteristic meets a prescribed criteria ~~The diafiltration module according to claim 2, further including:~~

a pinch valve disposed within the second conduit for controlling the flow of the substitution fluid through the second conduit, the pinch valve being in communication with the control unit.

8. (Previously Presented) The diafiltration module according to claim 7, further including:

a pressure transducer disposed within the second conduit downstream of the substitution fluid pump for detecting a pressure within

the second conduit, the pressure being the first detected characteristic, the pressure transducer in communication with the control unit, wherein the control unit controls the position of the pinch valve based on input received from the substitution fluid pump and the pressure transducer.

9. (Original) The diafiltration module according to claim 8, further including:

an optical sensor disposed within the second conduit downstream of the at least one sterilizing filter for detecting transmittance of fluid contained in the second conduit downstream of the at least one sterilizing filter, the optical sensor being in communication with the control unit, wherein the optical sensor includes a light source and a photo-detector to detect a loss of transmittance of light through the fluid contained with the second conduit downstream of the at least one sterilizing filter, wherein the control unit controls the position of the pinch valve also based on input received from optical sensor.

10. (Original) The diafiltration module according to claim 8, wherein the control unit signals the pinch valve to open when (a) the substitution fluid pump is operating and the diverted fluid is pumped within the second conduit towards the at least one sterilizing filter; and (b) the pressure transducer detects a minimum pressure that assures that the substitution fluid flow remains in a forward direction into the extracorporeal circuit when the pinch valve opens.
11. (Original) The diafiltration module according to claim 9, wherein the pinch valve is closed by the control unit when the optical sensor detects blood in the second conduit.
12. (Currently Amended) In a blood dialysis system including a dialysis machine and an extracorporeal circuit including a dialyzer, a diafiltration module that is an independent standalone unit relative to the dialysis



being inputted to the control unit for controlling the operation of the substitution fluid pump.

13. (Original) The diafiltration module according to claim 12, wherein the flow switch comprises one of a thermal flow switch and a mechanical flow switch.
14. (Currently Amended) In a blood dialysis system including a dialysis machine and an extracorporeal circuit including a dialyzer, a diafiltration module that is an independent standalone unit relative to the dialysis machine and the extracorporeal circuit and is adapted to be detachably connected to at least one of the dialysis machine and the extracorporeal circuit, the diafiltration module comprising:  
\_\_\_\_\_ a first conduit having a first end and an opposing second end, the first end for receiving a dialysate fluid from the dialysis machine and the second end for discharging the dialysate fluid to the dialyzer;  
\_\_\_\_\_ a second conduit in selective communication with the first conduit such that the second conduit selectively receives a diverted amount of the dialysate fluid from the first conduit, the second conduit communicating with at least one sterilizing filter for filtering the diverted amount of the dialysate fluid to produce a substitution fluid, wherein one end of the second conduit is configured to deliver the substitution fluid to the extracorporeal circuit; \_\_\_\_\_  
\_\_\_\_\_ a control unit responsive to a first detected characteristic of one of the dialysate fluid flowing within the first conduit and the diverted dialysate fluid flowing within the second conduit, the control unit being configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the first detected characteristic meets a prescribed criteria, wherein the control unit is responsive to a second detected characteristic of blood within the

extracorporeal circuit, the second detected characteristic being a flow rate of the blood, wherein the control unit is configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the second detected characteristic meets a prescribed criteria; and ~~The diafiltration module according to claim 3, further including:~~

a substitution fluid pump disposed within the second conduit for diverting the amount of the dialysate fluid from the first conduit to the second conduit, the substitution fluid pump being in communication with the control unit;

wherein the dialysis machine includes a blood pump disposed within the extracorporeal circuit for transporting blood through the extracorporeal circuit; and

wherein the second detected characteristic of blood comprises pressure pulses in the extracorporeal circuit, the detection of pressure pulses being inputted to the control unit to signal whether the blood pump is operating below a predetermined threshold value, the pressure pulses being processed by the control unit as feedback control input for controlling operation of the substitution pump.

15. (Previously Presented) The diafiltration module according to claim 14, wherein the extracorporeal circuit includes

a drip chamber disposed therein, the drip chamber having one or more pressure monitoring ports; and

a pressure transducer that is in fluid contact with one of the pressure monitoring ports of the drip chamber, the pressure transducer detecting the pressure pulses in the extracorporeal circuit.

16. (Original) The diafiltration module according to claim 14, further including:



one of the dialysate fluid flowing within the first conduit and the diverted dialysate fluid flowing within the second conduit, the control unit being configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the first detected characteristic meets a prescribed criteria, wherein the control unit is responsive to a second detected characteristic of blood within the extracorporeal circuit, the second detected characteristic being a flow rate of the blood, wherein the control unit is configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the second detected characteristic meets a prescribed criteria ~~The diafiltration module according to claim 2,~~ wherein the first detected characteristic is detected by a temperature decay measurement of at least one of the dialysate fluid in the first conduit and the diverted dialysate fluid in the second conduit.

20. (Currently Amended) In a blood dialysis system including a dialysis machine and an extracorporeal circuit including a dialyzer, a diafiltration module that is an independent standalone unit relative to the dialysis machine and the extracorporeal circuit and is adapted to be detachably connected to at least one of the dialysis machine and the extracorporeal circuit, the diafiltration module comprising:

\_\_\_\_\_ a first conduit having a first end and an opposing second end, the first end for receiving a dialysate fluid from the dialysis machine and the second end for discharging the dialysate fluid to the dialyzer;

\_\_\_\_\_ a second conduit in selective communication with the first conduit such that the second conduit selectively receives a diverted amount of the dialysate fluid from the first conduit, the second conduit communicating with at least one sterilizing filter for filtering the diverted



amount of the dialysate fluid to produce a substitution fluid, wherein one end of the second conduit is configured to deliver the substitution fluid to the extracorporeal circuit;

a control unit responsive to a first detected characteristic of one of the dialysate fluid flowing within the first conduit and the diverted dialysate fluid flowing within the second conduit, the control unit being configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the first detected characteristic meets a prescribed criteria, wherein the control unit is responsive to a second detected characteristic of blood within the extracorporeal circuit, the second detected characteristic being a flow rate of the blood, wherein the control unit is configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the second detected characteristic meets a prescribed criteria ~~The diafiltration module according to claim 3,~~ wherein the second detected characteristic is detected by a temperature decay measurement of the blood.

21. (Currently Amended) In a blood dialysis system including a dialysis machine and an extracorporeal circuit including a dialyzer, a diafiltration module that is an independent standalone unit relative to the dialysis machine and the extracorporeal circuit and is adapted to be detachably connected to at least one of the dialysis machine and the extracorporeal circuit, the diafiltration module comprising:

a first conduit having a first end and an opposing second end, the first end for receiving a dialysate fluid from the dialysis machine and the second end for discharging the dialysate fluid to the dialyzer;

a second conduit in selective communication with the first

conduit such that the second conduit selectively receives a diverted amount of the dialysate fluid from the first conduit, the second conduit communicating with at least one sterilizing filter for filtering the diverted amount of the dialysate fluid to produce a substitution fluid, wherein one end of the second conduit is configured to deliver the substitution fluid to the extracorporeal circuit;

a control unit responsive to a first detected characteristic of one of the dialysate fluid flowing within the first conduit and the diverted dialysate fluid flowing within the second conduit, the control unit being configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the first detected characteristic meets a prescribed criteria, wherein the control unit is responsive to a second detected characteristic of blood within the extracorporeal circuit, the second detected characteristic being a flow rate of the blood, wherein the control unit is configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the second detected characteristic meets a prescribed criteria ~~The diafiltration module according to claim 3,~~ wherein the first detected characteristic is calculated using a temperature decay measurement of one of the dialysate fluid and the diverted dialysate fluid and the second detected characteristic is calculated using a temperature decay measurement of the blood and the diafiltration module further includes:

a first temperature sensing device for detecting the temperature of one of the dialysate fluid in the first conduit and the diverted dialysate fluid in the second conduit, the first temperature sensing device in communication with the control unit and inputting the detected temperature to the control unit;

a second temperature sensing device for detecting the temperature of blood in the extracorporeal circuit, the second temperature sensing device in communication with the control unit and inputting the detected temperature to the control unit; and

wherein the control unit is configured to detect a decrease in flow rate of one of the dialysate fluid and the diverted dialysate fluid by monitoring the detected temperature inputted from the first temperature sensing device and a decrease in a blood flow rate within the extracorporeal circuit by monitoring the detected temperature inputted from the second temperature sensing device.

22. (Original) The diafiltration module according to claim 21, wherein the first temperature sensing device is disposed in one of (a) a location inside of the first conduit and (b) on an outer surface of the first conduit.
23. (Original) The diafiltration module according to claim 22, wherein the first temperature sensing device comprises one of a thermistor and thermocouple that is disposed inside of the first conduit.
24. (Original) The diafiltration module according to claim 21, wherein the second temperature sensing device is disposed in one of (a) a location inside of a conduit defining the extracorporeal circuit and (b) on an outer surface of the conduit defining the extracorporeal circuit.
25. (Original) The diafiltration module according to claim 20, wherein the temperature decay measurement is determined as one of (a) a change in temperature from a fixed set point and (b) a change in temperature per unit time.
26. (Previously Presented) The diafiltration module according to claim 22, wherein the first temperature sensing device comprises one of a





amount of the dialysate fluid to produce a substitution fluid, wherein one end of the second conduit is configured to deliver the substitution fluid to the extracorporeal circuit;

a control unit responsive to a first detected characteristic of one of the dialysate fluid flowing within the first conduit and the diverted dialysate fluid flowing within the second conduit, the control unit being configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the first detected characteristic meets a prescribed criteria, wherein the control unit is responsive to a second detected characteristic of blood within the extracorporeal circuit, the second detected characteristic being a flow rate of the blood, wherein the control unit is configured to prevent flow of substitution fluid to the extracorporeal circuit by controlling flow of the diverted dialysate fluid within the second conduit in the control module when at least the second detected characteristic meets a prescribed criteria The diafiltration module according to claim 3, wherein the control unit is configured to prevent flow of the substitution fluid to the extracorporeal circuit when at least one of the first and second detected characteristics meets a prescribed criteria, wherein the second detected characteristic is detected by monitoring a fluid level fluctuation of the blood within a drip chamber that is provided along the extracorporeal circuit and wherein the prescribed criteria is when the fluid level fluctuation is below an acceptable fluid level fluctuation value, thereby preventing the flow of substitution fluid to the extracorporeal circuit.

30. (Previously Presented) The diafiltration module according to claim 29, further including:

a substitution fluid pump disposed within the second conduit for diverting the amount of the dialysate fluid from the first conduit to the











37. (Canceled)

38. (Previously Presented) In a blood dialysis system including a dialysis machine that includes a source of dialysate fluid and an extracorporeal circuit, a method of preventing flow of substitution fluid to the extracorporeal circuit comprising the steps of:

providing a diafiltration module including a first conduit having a first end and a second end for carrying dialysate fluid and a second conduit in selective communication with the first conduit such that the second conduit selectively receives a diverted amount of the dialysate fluid, the diafiltration module further including at least one sterilizing filter in fluid communication with the second conduit for filtering the diverted dialysate fluid to produce the substitution fluid; fluidly connecting the first end of the first conduit to the dialysis machine so that the dialysate fluid flows from the source to the first conduit; fluidly connecting the second conduit to the extracorporeal circuit such that the substitution fluid is delivered and introduced into the extracorporeal circuit;

providing a control unit;

detecting a first characteristic of the dialysate fluid flowing within the first conduit and detecting a second characteristic of the blood flowing within the extracorporeal circuit; and

inputting the detected first and second characteristics to the control unit, wherein the control unit is configured to prevent the flow and introduction of the substitution fluid into the extracorporeal circuit when at least the first characteristic meets a prescribed criteria wherein the first characteristic comprises a flow rate of the dialysate fluid and the second characteristic comprises a flow rate of the blood and the prescribed criteria comprises a situation where the dialysate flow rate falls below a predetermined flow rate.

39. (Previously Presented) The method of claim 38, further including the step of:
- disposing a substitution fluid pump within the second conduit for diverting the amount of the dialysate fluid from the first conduit to the second conduit, wherein the control unit prevents the substitution fluid from being introduced into the extracorporeal circuit by controlling operation of the substitution fluid pump.
40. (Original) The method of claim 39, wherein detecting the first characteristic comprises the steps of:
- disposing a pressure transducer within the second conduit for detecting a pressure of the dialysate fluid within the second conduit; and transmitting a control signal from the control unit to the substitution fluid pump to turn to an OFF position when the pressure transducer detects a pressure below a threshold pressure value.
41. (Original) The method of claim 39, wherein detecting the first characteristic comprises the steps of:
- disposing a pressure transducer within the second conduit for detecting a pressure of the dialysate fluid within the second conduit; disposing a pinch valve within the second conduit for controlling the flow of the substitution fluid within the second conduit; and transmitting a control signal from the control unit to the pinch valve to position the pinch valve in response to the control unit receiving input from the substitution fluid pump and the pressure transducer.
42. (Original) The method of claim 41, further including the step of:
- disposing an optical sensor disposed within the second conduit for detecting transmittance of fluid contained in the second conduit; and positioning the pinch valve by transmitting a control signal to the pinch

valve from the control unit in response to input received by the control unit from the optical sensor.

43. (Original) The method of claim 42, further including the step of: closing the pinch valve when the optical sensor detects blood in the second conduit.
44. (Original) The method of claim 39, further including the steps of:  
disposing a flow switch within the first conduit for detecting a flow rate within the first conduit; and  
controlling the operation of the substitution fluid pump based on a position of the flow switch.
45. (Previously Presented) The method of claim 38, wherein detecting the first and second characteristics comprise the steps of:  
performing a first temperature decay measurement of the dialysate fluid in the first conduit, the first temperature decay measurement being representative of a flow rate of the dialysate fluid;  
performing a second temperature decay measurement of the blood in the extracorporeal circuit, the second temperature decay measurement being representative of a flow rate of the blood; and  
wherein the control unit is configured to detect a decrease in the flow rate of the dialysate fluid by monitoring the first temperature decay measurement and a decrease in the flow rate of the blood by monitoring the second temperature decay measurement.
46. (Previously Presented) The method of claim 38, wherein the first detected characteristic is detected by inductively monitoring a current applied to an inlet valve of the dialysis machine that is disposed within a conduit that carries the dialysate fluid to the first conduit and wherein the second detected characteristic is detected by inductively monitoring a

current applied to a motor that drives a blood pump disposed within the extracorporeal circuit.

47. (Canceled)

48. (Canceled)

49. (New) The diafiltration module according to claim 7, further including a substitution fluid pump disposed within the second conduit upstream of the at least one sterilizing filter for diverting the amount of the dialysate fluid from the first conduit to the second conduit, the substitution fluid pump being in communication with the control unit.